

### APPLICATIONS

- Foreground Music & Paging Systems
- Theme Bars
- Theme Parks
- Audio Visual
- Boardrooms & Offices
- Airports, Convention Centres & Hotels
- Houses of Worship
- Cruise ships
- Retail Outlets

### FEATURES

- Point Source Transducer
- Compact moulded cabinet
- Constant Directivity
- 60° conical dispersion pattern
- High Sensitivity
- Integral flying points for ease of installation
- Yoke, and bracket mounting options
- i5T AW – Multi-Tap Voltage & Wattage through a THP30 line transformer
- Weatherproof to IP33CS in EN60529
- Five year warranty



The i5 AW is the latest addition to the Tannoy range of All Weather installation loudspeakers. Suited to applications indoors or out the i5 AW delivers a consistently powerful performance under a wide range of environmental conditions.

Available in charcoal grey or white, this compact loudspeaker has been optimally tuned to achieve maximum bass response and tonal balance, and will blend effectively into most backgrounds.

The Point Source ICT™ drive unit allows the i5 AW to be mounted from a wall or ceiling either horizontally or vertically without affecting its performance. A range of hardware options ensures simple and effective installation.

The i5 AW is also available in a transformer version (i5T AW), for use in 70.7V or 100V line systems.



## TECHNICAL SPECIFICATIONS

Frequency Response (1)	80Hz – 22kHz	
Power Handling (2)	Average:	50 watt
	Programme:	100 watt
	Peak (10ms):	200 watt
Sensitivity (1) 2.83v @ 1m	90 dB (Anechoic) 93 dB (Half Space)	
Maximum SPL (3) @ 1m	Average:	107dB (Anechoic) 110dB (Half space)
	Peak:	113dB (Anechoic) 116dB (Half space)
Impedance	Nominal:	6 Ω
	Minimum:	3.8 Ω
Dispersion	60° conical	
Driver Complement	1 x 5" (127mm) ICT™	
Enclosure	4.6 litre polypropylene	
Finish	Charcoal grey/white	
Protective Grille	Perforated steel, with 58% free airflow	
Connectors	2 x 4mm binding posts	
Fittings	Fixing points for MB5 mounting options	
Dimensions (HxWxD)	223.5mm x 162.6mm x 153mm – each (8.81" x 6.41" x 6.03") – each	
Weight	i5 AW	2.0kg (4.4 lbs) – each
	i5T AW	2.4kg (5.28 lbs) – each
Accessories (optional)	MB5Y – yoke, MB5B – wall bracket	
Shipping dimension:	425mm x 280mm x 215mm – pair (8.46" x 16.73" x 11.02") – pair	
Shipping Weight	i5 AW	4.5 kg (9.9 lbs) – pair
	i5T AW	5.7kg (12.54 lbs) – pair

(1) Average over stated bandwidth. Measured at 1m on axis in an anechoic chamber

(2) Long term power handling capacity as defined in EIA standard RS-426A

(3) Unweighted pink noise input, measured at 1m

Tannoy operates a policy of continuous research and development. The introduction of new materials or manufacturing methods will always equal or exceed the published specifications, which Tannoy reserves the right to alter without prior notice. Please verify the latest specifications when dealing with critical applications

**Tannoy Ltd.**, Professional Division, Coatbridge, ML5 4TF, Scotland  
Tel: +44 (0)1236 420199 Fax: +44(0)1236 428230  
e-mail: [prosales@tannoy.com](mailto:prosales@tannoy.com) Internet site: <http://www.tannoy.com>

**TGI North America**, 300 Gage Avenue, Unit One, Kitchener, Ontario, N2M 2C8, Canada  
Tel: (519) 745 1158 Fax: (519) 745 2364

**Tannoy Nederland b.v.**, Anthonetta Kuyjlstraat 19, 3066 GS Rotterdam  
Tel: (010) 2860554 Fax: (010) 2860431

